

# DURATRON® T4501 PAI

## Longer Production Life, lower Maintenance for Rollers supporting large Coffee Roaster Drum



### TRENDS

High volume production requirements of the food and beverage processing industry require equipment manufacturers to find ways to increase the life and up-time of the machinery they offer. These improvements can provide them a competitive marketing advantage on cost-in-use for their customers. At the same time, increased production often means higher temperatures and speeds for components used in their equipment, creating premature failure of components and affecting overall machine performance.

### QEPP ANSWERS

Quadrant was asked by an equipment manufacturer for solutions to a wear problem that affected the sales of their commercial coffee roasting equipment. When the urethane-encased metal rollers that supported the roasting drums experienced wear and corrosion they created increased noise during operation and premature drum failure. Quadrant recommended rollers machined from DURATRON® T4501 PAI. Result: the equipment manufacturer gained marketable advantages in noise reduction, production life and reliability.

### CUSTOMER BENEFITS

The DURATRON® T4501 PAI rollers eliminated the harsh noise being created by metal-on-metal contact. They also improved in-service life by eliminating corrosion problems and drum damage. The unique high strength at high temperatures of DURATRON® PAI also easily withstood the roasting temperatures, and its wear properties eliminated the need for any external lubrication.



QUADRANT

You inspire ... we materialize®

# COMPRESSION MOULDED

Application and its requirements	DURATRON® T4501 PAI performance
Rollers supporting and turning a large coffee roasting drum must withstand the high loads and roasting temperatures without significant wear.	Self-lubricating DURATRON® PAI used for the machined rollers provides excellent wear properties for extended life and no risk of wear-related damage to the costly roaster drum.
Temperatures inside the drum reached 260°C to 370°C. Thermal transfer to the bearing, coupled with a loaded drum weighing up to 1812 kg (453 kg per roller), created flat spots after a very short time.	DURATRON® PAI maintains its strength at high temperatures and offers the best creep resistance under load for when the drum sat idle - even at process temperatures.
Noise is a major factor in any plant environment. When the urethane cap on the metal rollers quickly wore out, harsh metal-to-metal noise resulted.	DURATRON® PAI in contact with metal runs much quieter to eliminate the need for heavy duty hearing protection.

### Other material candidates:

- KETRON® PEEK: insufficient creep resistance under load at temperatures above 160°C.
- Vespel® SP21: Less strength at temperatures, higher wear, far higher material costs vs.

All information supplied by or on behalf of Quadrant Engineering Plastic Products in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but Quadrant Engineering Plastic Products assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to Quadrant Engineering Plastic Products for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.

VESPEL® is a registered trademark of DuPont.  
 DURATRON® and KETRON® are registered trademarks of the Quadrant Group.



Learn more online at  
[www.quadrantplastics.com](http://www.quadrantplastics.com)

Quadrant has extensive product and machining resources available online. Our website is a portal to a wealth of technical data and the easiest way to engage our application specialists. Our team stands ready to help offer solutions to your toughest problems.

Distributed by



**Alpert Engineering Ltd**

Dublin Industrial Estate,  
 Glasnevin, Dublin11, Ireland  
[www.alpert.com](http://www.alpert.com) [info@alpert.com](mailto:info@alpert.com)  
 Phone +353 1 8306277