

DURATRON® T4503 PAI

Long Life Spray Nozzles for Automotive Electrostatic Body Paint Systems



TRENDS

To compete in the world market, automotive manufacturers and the companies that supply their manufacturing systems face the challenges of high productivity, high quality and cost competitiveness. When an equipment manufacturer engaged Quadrant to help design a spray nozzle for an electrostatic coating system that could withstand the aggressive environment and increase in-service life, DURATRON® PAI was the recommended candidate for the precision machined components.

QEPP ANSWERS

The wear resistance and electrical properties of DURATRON® PAI, coupled with its extreme dimensional stability allowed a much simpler nozzle design. The machined part eliminated the costly downtime associated with shorter service life due to wear, and more frequent shut down for cleaning. Also, the cleaning process and agents posed no problem for DURATRON® PAI, allowing quick change-over between production runs.

CUSTOMER BENEFITS

The newly designed, machined DURATRON® T4503 PAI nozzle easily handles the aggressive paint systems and cleaners, while providing the mechanical strength needed to spin at speeds above 60,000 rpm. The light weight of DURATRON® PAI coupled with its strength and stability gave the system's builders a two-fold marketing advantage. The new nozzles needed less cleaning - which equated to a lower maintenance cost and allowed the end customer to increase production uptime, an equally valuable benefit.



QUADRANT

You inspire ... we materialize®

SEALING IN LIQUID EPOXY, CURED

Application requirements	DURATRON® T4503 PAI performance
The parts spin at very high rotation (60,000 rpm up to 85,000 rpm).	DURATRON® T4503 PAI maintains its dimensions and critical tolerances, due to its dimensional stability and creep resistance, even under extreme centrifugal loading conditions.
Paint particles move through the nozzle at a high rate of speed essentially “sand-blasting” the nozzle.	DURATRON® PAI has excellent wear resistance and its hardness helps deflect the particles resulting in increased service life.
Nozzles are aggressively cleaned after each use to ensure no remaining will interfere with the next production run.	The chemical resistance of DURATRON® PAI withstands the aggressive cleaning agents with no degradation.

Other material candidates:

- Ceramics: Extremely brittle; prone to frequent cracking during handling and installation.
- 30% Carbon-filled PEEK®: lacks hardness and wear resistant compared to DURATRON® PAI.

All information supplied by or on behalf of Quadrant Engineering Plastic Products in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but Quadrant Engineering Plastic Products assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to Quadrant Engineering Plastic Products for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.

DURATRON® and **KETRON®** are registered trademarks of the Quadrant Group.



Learn more online at
www.quadrantplastics.com

Quadrant has extensive product and machining resources available online. Our website is a portal to a wealth of technical data and the easiest way to engage our application specialists. Our team stands ready to help offer solutions to your toughest problems.

Distributed by



Alpertron Engineering Ltd

Dublin Industrial Estate,
Glasnevin, Dublin11, Ireland
www.alpertron.com info@alpertron.ie
Phone +353 1 8306277